ARRIS LUMBER COMPANY

Timber Catalog KD DF #1&BTR RESAWN FOHC

3X6	12' 16' 20'	Janka Hardness: 660
3X8	12' 16' 20'	Strength (MOR): 12,400 psi
3X10	12' 16' 20'	
3X12	12' 16' 20'	Stiffness (MOE): 1,950,000 psi
4X4	8' 10' 12' 14' 16' 20'	Density (KG/m3): 530
4X6	12' 16' 20'	Photosensitivity: Moderate
4X8	12' 16' 20'	
4X10	12' 16' 20'	Tangential Shrinkage: 7.9%
4X12	12' 16' 20'	Radial Shrinkage: 4.2%
6X6	8' 10' 12' 14' 16' 20'	Family: Pinaceae
6X8	12' 16' 20'	
6X10	12' 16' 20'	Height: 150' to 200'
6X12	12' 16' 20'	Diameter: 2' to 6'
8X8	8' 10' 12' 14' 16' 20'	Weight: 32 lbs per cubic foot
8X10	12' 16' 20'	
8X12	12' 16' 20'	
10X10	8' 10' 12' 14' 16' 20'	
10X12	12' 16' 20'	
12X12	8' 10' 12' 14' 16' 20'	
	Oversized timbers and long lengths are available for special order.	